Sand Micro™

Mineral Fiber Ceilings

VOC

\$\$\$\$

LEED[®] v4

- MR: Environmental Product
 Declarations (EPDs)
- MR: Sourcing Raw Materials
- MR: Material Ingredients (HPDs)
- IEQ: Daylight
- IEQ: Low-Emitting Materials
- IEQ: Prereq. Min. Acoustic Performance (Schools)
- IEQ: Acoustic Performance
- MR: PBT Source Reduction (Healthcare)
- IEQ: Interior Lighting
- EA: Prereq. Min. Energy Performance
- EA: Optimize Energy Performance
- Recycled Content
 Pre: 28% | Post: 2%

TOOLS

Visit CertainTeed.com/Ceilings Download HPDs and EPDs LEED® Information / BIM Objects 3-Part Specs / Data Pages



Resource Content Recycled Content

Carbon Footprint Reduction Rapidly Renewable



0





FEATURES & BENEFITS

- Non-directional visual
- High humidity and sag resistant
- Third-party verified Environmental Product Declaration (EPD) available for this product
- Lightly textured surface provides attractive finish with excellent light reflectance and enhanced durability
- Health Product Declaration (HPD) available for this product


APPLICATIONS

- Schools
- Retail / Department Stores

CertainTee

- Corridors
- Hospitality Spaces
- Other Commercial Buildings / Space Applications

AVAILABLE EDGE DETAILS





CertainTeed Ceilings | Acoustic Ceilings & Suspension Systems



Sand Micro™ Reveal (SHM-154)

| ATTRIBUTES | | | \otimes | « ((v | EPD | HPD | 1 | 0 | | \sim | * | LOW VOC | 0 |
|----------------------------------|------------------------|----------------|---------------|-------|------------------|------------------|------------------|-------------------|------|----------|----------------------------|-----------------------|---------------------|
| | DIMENSIONS (INCHES) | EDGE DETAIL | UL CLA NRC | | EPD AVAILABLE | HPD AVAILABLE | SAG RESISTANT | MOLD RESISTANT | LR | WASHABLE | FIRE CLASS (ASTM E1264) | EMISSION COMPLIANT | RECYCLED CONTENT |
| SAND MICRO™ | | | | | | | | | | | | | |
| SHM-157 | 24 x 24 x 5/8 | Trim | 0.50 | 33 | Yes | Yes | Yes | BioShield | 0.88 | _ | Class A | Certified | 30% |
| SHM-154 | 24 x 24 x 5/8 | Reveal | 0.50 | 33 | Yes | Yes | Yes | BioShield | 0.88 | _ | Class A | Certified | 30% |
| SHM-150 | 24 x 24 x 5/8 | Narrow Reveal | 0.50 | 33 | Yes | Yes | Yes | BioShield | 0.88 | - | Class A | Certified | 30% |
| SHM-197 | 24 x 48 x 5/8 | Trim | 0.50 | 35 | Yes | Yes | Yes | BioShield | 0.88 | _ | Class A | Certified | 30% |
| SHM-194 | 24 x 48 x 5/8 | Reveal | 0.50 | 35 | Yes | Yes | Yes | BioShield | 0.88 | _ | Class A | Certified | 30% |
| SHM-190 | 24 x 48 x 5/8 | Narrow Reveal | 0.50 | 35 | Yes | Yes | Yes | BioShield | 0.88 | _ | Class A | Certified | 30% |
| SAND MICRO [™] - METRIC | | | | | | | | | | | | | |
| SHM-154M | 600 x 600 x 15 | Reveal | 0.50 | 33 | Yes | Yes | Yes | BioShield | 0.88 | _ | Class A | Certified | 30% |
| SHM-150M | 600 × 600 × 15 | Narrow Reveal | 0.50 | 33 | Yes | Yes | Yes | BioShield | 0.88 | _ | Class A | Certified | 30% |

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

PHYSICAL DATA

MATERIAL Mineral Fiber

ASTM E1264 CLASSIFICATION Type III, Form 2, Pattern C E

FIRE CLASS (ASTM E1264) Tested according to ASTM E84 & CAN S102 Flame Spread: 25 or less Smoke Developed: 50 or less

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010.

MOLD/MILDEW RESISTANCE

BioShield[®] treatment included for added mold and mildew resistance.

MAINTENANCE Wipe with a soft cloth or vacuum with brush attachment. WARRANTY 10-year 104/90 Limited Warranty



Technical Support | certainteed.com/ceilings 800-233-8990 © 05/18 CertainTeed Corporation