SYMPHONY® m Rx | SYMPHONY® m Rx High NRC

Smooth Mineral Fiber

The Symphony m Rx line provides a white, clean, monolithic ceiling visual. Design with other products in the Symphony Rx line for acoustical solutions.



FEATURES AND BENEFITS

- Superior noise reduction to maximize inter-zone attenuation
- Outstanding acoustical value, high light reflectance and humidity resistance
- Exceptional durability
- Superior stain resistance and water repellency
- Washable with most sanitizing solutions and wash-tested to 2,000 wash cycles
- Satisfies USDA/FSIS guidelines for sanitary applications (commercial kitchens)
- Exceeds FGI guidelines for cleanability and acoustic performance in most healthcare applications
- Approved for use in federally registered Canadian food establishments
- Suited as clean room component to ISO Class 3 (highest among comparable products)
- High USDA Certified Biobased content at 98%
- Declare Label / LBC Red List Free

SUSPENSION SYSTEM OPTIONS











LEED® v4

RECYCLED CONTENT

62%

✓ EA: Optimize Energy Performance

EA: Prereq. Min. Energy Performance

✓ EQ: Interior Lighting

✓ MR: PBT Source Reduction (Healthcare)

✓ EQ: Acoustic Performance

EQ: Prereq. Min. Acoustic Performance

✓ EQ: Low-Emitting Materials

✓ EQ: Daylight

✓ MR: Material Ingredients (HPDs)

MR: Sourcing Raw Materials

MR: Environmental Product Declarations (EPDs)

MR: Construction and Demolition Waste

LEED* is a registered trademark of the U.S. Green Building Council.





EPD Available



DeclareSM
Living Building Challenge Red List Free®
DeclareSM is a service mark of The
International Living Future Institute.



SYMPHONY® m Rx | SYMPHONY® m Rx High NRC

Smooth Mineral Fiber

All products in this line feature these attributes:















YMPHONY <i>m</i> Rx High NRC			Format	Dimensions (in.)	NRC	CAC	Recycled Content	Pieces/ carton	Sq. Ft./ carton	Lbs./ carton	Cartons/ pallet
TRIM											
	80	1222-80-RXS-1	Panels	24 x 24 x 7/8	0.80	35	62%*	16	56	64	16
	NRC	1220-80-RXS-1	Panels	24 x 48 x 7/8	0.80	35	62%*	8	64	74	14
REVEAL											
	88	1222B-80-RXS-1	Panels	24 x 24 x 7/8	0.80	35	62%*	16	56	64	16
	NRC	1220B-80-RXS-1	Panels	24 x 48 x 7/8	0.80	35	62%*	8	64	74	14
NARROW REVEAL											
	88	1222F-80-RXS-1	Panels	24 x 24 x 7/8	0.80	35	62%*	16	56	64	16
	NRC	1220F-80-RXS-1	Panels	24 x 48 x 7/8	0.80	35	62%*	8	64	74	14

^{*}Manufacturer certified pending independent confirmation

SYMPHONY m R	X		Format	Dimensions (in.)	NRC	CAC	Recycled Content	Pieces/ carton	Sq. Ft./ carton	Lbs./ carton	Cartons/ pallet
TRIM											
	NRC 75	1222-75-RXS-1	Panels	24 x 24 x 3/4	0.75	36	62%	16	56	47	20
	¥	1220-75-RXS-1	Panels	24 x 48 x 3/4	0.75	36	62%	8	64	64	16
	NRC 70	1222-RXS-1	Panels	24 x 24 x 3/4	0.70	35	62%	16	56	47	20
	R S	1220-RXS-1	Panels	24 x 48 x 3/4	0.70	35	62%	8	64	64	16
REVEAL											
	NRC 75	1222B-75-RXS-1	Panels	24 x 24 x 3/4	0.75	36	62%	14	56	56	16
	N N	1220B-75-RXS-1	Panels	24 x 48 x 3/4	0.75	36	62%	8	64	64	16
	NRC 70	1222B-RXS-1	Panels	24 x 24 x 3/4	0.70	35	62%	14	56	56	16
	N N N	1220B-RXS-1	Panels	24 x 48 x 3/4	0.70	35	62%	8	64	64	16
NARROW REVEAL											
	NRC 75	1222F-75-RXS-1	Panels	24 x 24 x 3/4	0.75	36	62%	14	56	56	16
	N N	1220F-75-RXS-1	Panels	24 x 48 x 3/4	0.75	36	62%	8	64	64	16
	NRC 70	1222F-RXS-1	Panels	24 x 24 x 3/4	0.70	35	62%	14	56	56	16
	NR	1220F-RXS-1	Panels	24 x 48 x 3/4	0.70	35	62%	8	64	64	16

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

SYMPHONY m Rx ACCESSORIES Product Name Pieces/carton Use



1170-SEL-1

Mineral Fiber Edge Sealant

For re-sealing cut edges; 1 quart container



SYMPHONY® m Rx | SYMPHONY® m Rx High NRC

Smooth Mineral Fiber

PHYSICAL DATA

MATERIAL Mineral Fiber

ASTM E1264 CLASSIFICATION Type IV, Form 2, Pattern E

FIRE CLASS (ASTM E1264) All are Class A per ASTM E84 & CAN S102 Flame Spread: 25 or less Smoke Developed: 50 or less

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

MOLD/MILDEW RESISTANCE BioShield* treatment included for added mold and mildew resistance.

MAINTENANCE

Wash tested to 2,000+ cycles. Cleanable with sanitizing chemicals.

WARRANTY

10-year 104/90 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/ceilings.

